

LAGERPROGRAMM *STOCK PROGRAM*

FIRMENGRUPPE / GROUP OF COMPANIES



Patroonelementen standaard KIT

LAGERPROGRAMM

STOCK PROGRAM

Heizpatronen

Cartridge Heaters

	PE	PDE	PDS	PDZ	PDH	PZH	HPS	HPZ	0
Einsatztemperatur¹⁾ <i>operating temperature¹⁾</i>	400 °C	500 °C	750 °C	750 °C	750 °C	750 °C	750 °C	750 °C	600 °C
max. Leistungsdichte <i>max load</i>	4 W/cm ²	10 W/cm ²	15 W/cm ²	15 W/cm ²	20 W/cm ²	20 W/cm ²	30 W/cm ²	30 W/cm ²	4 W/cm ²
Masseinheit <i>scale unit</i>	mm	mm	mm	Zoll <i>inch</i>	mm	Zoll <i>inch</i>	mm	Zoll <i>inch</i>	mm

¹⁾ max. am Patronenmantel / max at cartridge surface

weitere Informationen entnehmen Sie bitte den Technischen Daten / for further informations please see as well technical data

∅	Patronenlänge in mm / Cartridge length in mm												
	50	60	80	100	130	150	160	180	200	225	250	275	300
6,5 mm PDS	auf Anfrage / on request	100 W	100 W	100 W	220 W	350 W							
		125 W	125 W	160 W	300 W	400 W							
		150 W	150 W	200 W	350 W								
		160 W	160 W	220 W	390 W								
		180 W	250 W	300 W									
8,0 mm PDE		125 W	160 W	180 W	250 W		200 W						
		140 W	200 W	200 W	315 W								
		150 W		250 W									
		160 W		280 W									
		180 W		315 W									
		200 W		370 W									
8,0 mm PDS	140 W	125 W	160 W	180 W	250 W	410 W	200 W						
	160 W	140 W	200 W	200 W	315 W	500 W							
		150 W	220 W	250 W	350 W								
		160 W	250 W	280 W	400 W								
		180 W		315 W									
		200 W		370 W									
8,0 mm PDH				350 W	450 W		500 W						
				400 W	500 W		600 W						
10,0 mm PDE	100 W	125 W	100 W	125 W	250 W	210 W	200 W		290 W	300 W	370 W	410 W	450 W
	160 W	140 W	160 W	135 W	315 W	340 W	400 W		300 W	525 W	400 W	650 W	500 W
		150 W	200 W	180 W	400 W		500 W		400 W	670 W	590 W		710 W
		160 W	220 W	200 W	450 W		630 W		465 W	800 W	630 W		
		180 W	250 W	210 W	500 W	700 W	700 W		600 W	900 W	700 W		
		200 W	300 W	220 W	580 W				630 W	1050 W	800 W		
		220 W	315 W	250 W					700 W		900 W		
		260 W	370 W	280 W					820 W		1000 W		
		300 W		315 W							1150 W		
				350 W									
				400 W									
				520 W									
10,0 mm PDH					750 W		800 W	850 W	800 W				
							900 W	900 W	1000 W				

Änderungen + Zwischenverkauf vorbehalten / Subject to change and prior sale

Lagerliste kpl. 04/18



info@wilmod.nl
www.wilmod.nl

Amethystweg 39 \ 2665 NT Bleiswijk
T +31 79 346 19 19

info@kuwatec.nl
www.kuwatec.nl

Wilmod
heating & systems

Patroonelementen standaard KIT

LAGERPROGRAMM

STOCK PROGRAM

Ø	Patronenlänge in mm / Cartridge length in mm												
	50	60	80	100	130	150	160	180	200	225	250	275	300
12,5 mm PDE	100 W 160 W 200 W	125 W 160 W 200 W 250 W	120 W 150 W 195 W 200 W 250 W 300 W 315 W	160 W 200 W 250 W 315 W 400 W	250 W 400 W 500 W	255 W 405 W	300 W 500 W 600 W 630 W	670 W	350 W 400 W 555 W 630 W 700 W	395 W 630 W	440 W 705 W 800 W 900 W	490 W 780 W	535 W 600 W 860 W
12,5 mm PDS	100 W 160 W 200 W 220 W 250 W 300 W	125 W 160 W 200 W 250 W 280 W 330 W 380 W	120 W 150 W 195 W 200 W 250 W 300 W 315 W 400 W 430 W 470 W	160 W 200 W 250 W 315 W 400 W 430 W 510 W 600 W	250 W 400 W 500 W 550 W 630 W 730 W	255 W 405 W 650 W 750 W 880 W	300 W 500 W 600 W 630 W 700 W 800 W 880 W	670 W 800 W 900 W 1050 W	350 W 400 W 555 W 630 W 700 W 900 W 1000 W 1020 W	395 W 630 W 1000 W 1150 W 1300 W	440 W 705 W 800 W 900 W 1100 W 1250 W 1450 W	490 W 780 W 1200 W 1400 W 1600 W	535 W 600 W 860 W 1400 W 1750 W
12,5 mm PDH			500 W 630 W		1000 W		1000 W 1250 W	1000 W 1400 W	800 W 1500 W		1000 W 1250 W		1500 W 2000 W
16,0 mm PDE	160 W 200 W 250 W	160 W 200 W 250 W 315 W	180 W 200 W 280 W 315 W 400 W	230 W 300 W 350 W 360 W 400 W 500 W	400 W 500 W 630 W 630 W	350 W 560 W	500 W 630 W 700 W 800 W	850 W	480 W 500 W 600 W 760 W 800 W 1000 W	540 W 860 W	600 W 700 W 1000 W 1250 W	670 W 1060 W	730 W 1000 W 1160 W 1250 W 1500 W
16,0 mm PDS	160 W 200 W 250 W 270 W 315 W 380 W	160 W 200 W 250 W 315 W 360 W 420 W 490 W	180 W 200 W 280 W 315 W 400 W 450 W 500 W	230 W 300 W 350 W 360 W 400 W 500 W 600 W 700 W 750 W	400 W 500 W 630 W 700 W 800 W 940 W	350 W 560 W 850 W 1000 W 1100 W	500 W 630 W 700 W 800 W 900 W 1000 W 1100 W	850 W 1000 W 1250 W 1300 W	480 W 500 W 600 W 760 W 800 W 1000 W 1100 W 1250 W 1500 W	540 W 860 W 1300 W 1450 W 1650 W	600 W 700 W 960 W 1000 W 1250 W 1400 W 1600 W 1875 W	670 W 1060 W 1600 W 1800 W 2050 W	730 W 1000 W 1160 W 1250 W 1500 W 1800 W 2000 W 2250 W
16,0 mm PDH			800 W	1000 W			1600 W	1800 W	2000 W		2000 W		2000 W
20,0 mm PDS	380 W 420 W 470 W	450 W 510 W 570 W	600 W 680 W 750 W	800 W 850 W 900 W	900 W 1100 W 1200 W	1000 W 1250 W 1400 W	1000 W 1250 W 1500 W	1350 W 1500 W 1650 W	1500 W 1600 W 1800 W	1650 W 1900 W 2100 W	1900 W 2300 W	2050 W 2300 W 2500 W	2250 W 2600 W
20,0 mm PDH	315 W 400 W	630 W	1000 W	1400 W	1800 W		1800 W	1900 W	2000 W 2500 W		2000 W 2500 W		2200 W 2500 W

Änderungen + Zwischenverkauf vorbehalten / Subject to change and prior sale

Lagerliste kpl. 04/18



info@wilmod.nl
www.wilmod.nl

Amethystweg 39 \ 2665 NT Bleiswijk
T +31 79 346 19 19

info@kuwatec.nl
www.kuwatec.nl

Wilmod
heating & systems